

AD-500



Single or multiple head high intensity flash system



The Specialised Imaging AD-500 Flash system offers the flexibility of up to four controllable high intensity flash heads for use in scientific and industrial environments.

500J Flash head with 2ms duration

Up to four independent flash heads

40s recycle time

Trigger options - short or positive edge

CONTROL UNIT

Signal Input	Four independent Channels
Trigger Mode	1. Independent - All channels trigger separately 2. Simultaneous - Any channel triggers all channels
Trigger Source	Short Circuit 5-100V positive edge
Input Impedance	50Ω
Mains Input	IEC socket
Electrical input	Mains 100-240V AC 50-60Hz
Dimensions mm	(LxWxH) 220mm x 110mm x 128mm
Weight	3.7kg
EMC	Meets all UKCA/EU harmonised standards

FLASH HEAD

Light Duration (Typ)	2ms measured to 50% of peak output
Stored Charge (max)	500J
Charge Voltage	340V
Light Source	U-Shape Xenon flashtube
Rise Time	50μs
Delay (typ)	30μs
Recycling Time (typ)	40 seconds
Dimensions	(LxDia) 270mm x 170mm
Weight (Kg)	5.25kg
Lamp cable length	2.5m
EMC	Meets all UKCA/EU harmonised standards

UK (Head Office / Factory)

6 Harvington Park,
Pitstone Green Business Park
Pitstone. LU7 9GX England

Tel +44 (0) 1442 827728

USA

Specialised Imaging Inc.
40935 County Center Dr. Suite D
Temecula, CA 92591, USA

Tel +1 951-296-6406

GERMANY

Bahnhofstr. 26 D
82256 Fürstenfeldbruck
Germany

Tel +49 8141 6668 922



FM 87429

specialised-imaging.com info@specialised-imaging.com